

ALFA 35 Superfast



SEMIAUTOMATIC BORING MACHINE -- 35 SPINDLES

CHARACTERISTICS

- 35 quick-change spindles
- Pneumatic cylinder for horizontal/vertical positioning of the boring group (45° & any intermediate angles)
- Side reference fences with digital electronic readout
- Front caliper with digital electronic readouts
- 2 aluminum fences (1500 mm each) with 2 stops each
- 2 safety clamps inclined 4°
- Height regulation of the boring group by mechanical digital position indicator
- 6 positions turret to adjust the drilling depth (0-80 mm)
- Automatic vertical-horizontal depth difference device (10 mms)
- Drilling speed adjustment from the panel control
- Strengthened steel structures for tilting of the boring group
- 1 motor 3 HP (Kw 2,2)
- Start/stop electropneumatic circuit by means of the foot pedal
- Standard accessories
 - ❖ Profile aluminum bar 3000 mm. length, complete with 4 stops, with possibility to exclude single stops
 - ❖ Rapid chuck suitable to receive bits with cylindrical attachment diam. 10 mms
 - ❖ Reference block
 - ❖ Special device for symmetric left & right positioning of the side fences to connect with a reference block
 - ❖ Supplementary clamp



CE STANDARDS

OPTIONS

- Miter frame fence 45°
- Rapid chuck suitable to receive bits with cylindrical attachment; diameter 10 mms
- Supplementary clamp
- Supplementary stop
- Pointing laser for multiple rows of holes
- Head for hinges int.48/6 (SALICE)
- Head for hinges int. 45/9,5 (BLUM)
- Head for hinges int.42/11 (GRASS)
- Head for hinges int.52/5,5 (HETTICH)
- Head for hinges int.48/9 (MEPLA)
- Head for hinges int.38/7,5 (MINI)
- Head for hinges int.52/7,5